

# Capital

SINCE 1936

## The Windsor Series COMMERCIAL & INDUSTRIAL WATER CONDITIONERS



APARTMENT BUILDINGS  
BOILER TREATMENT  
CAR WASHES  
COMMERCIAL BUILDINGS  
CONDOMINIUMS  
FACTORIES  
HEALTH CLUBS

HOSPITALS  
LAUNDRIES  
MOTELS & HOTELS  
NURSING AND REST HOMES  
OFFICE BUILDINGS  
RESTAURANTS  
SCHOOLS

*"You never had it so soft!"*

## SPECIFICATIONS


Model WS-125	Mineral Tank Inches	Brine Tank Inches	Salt Storage Lbs.	Shipping Weight Lbs.	WS-125 Pipe Inches
32	9x48	18x33	200	120	1.25"
48	10x54	18x33	175	150	1.25"
64	13x54	18x40	300	260	1.25"
96	14x65	24x41	525	315	1.25"
128	16x65	24x41	525	420	1.25"
160	18x65	24x50	510	535	1.25"

## SPECIFICATIONS

Model WS-125	Gravel Lbs.	Resin Cu. Ft.	Flow Rate Cont. 15 PSI Drop	Flow Rate Cont. 25 PSI Drop	BKW GPM
32	9	1.0	19.0	28.0	2.2
48	10	1.5	19.0	28.0	2.7
64	35	2.0	25.0	34.0	3.2
96	39	3.0	24.0	33.0	4.2
128	50	4.0	25.0	34.0	5.3
160	50	5.0	27.0	35.0	6.5

## CAPACITY CHART

Model WS-125	Rated Capacity Low Salt Grains @ Lbs	Rated Capacity Medium Salt Grains @ Lbs	Rated Capacity High Salt Grains @ Lbs
32	20,000 @ 6.0	24,000 @ 8.0	32,000 @ 15.0
48	30,000 @ 9.0	36,000 @ 12.0	48,000 @ 22.5
64	40,000 @ 12.0	48,000 @ 16.0	64,000 @ 30.0
96	60,000 @ 18.0	72,000 @ 24.0	96,000 @ 45.0
128	80,000 @ 24.0	96,000 @ 32.0	128,000 @ 60.0
160	100,000 @ 30.0	120,000 @ 40.0	160,000 @ 75.0



DIMENSIONS					
WS-125	A	B	C	D	
32	18	33	9	56	
48	18	33	10	62	
64	18	40	13	62	
96	24	41	14	73	
128	24	41	16	73	
160	24	50	18	73	

## OPERATING CONDITIONS

1. Temperature not to exceed 110° and should not be subject to freezing.
2. Water pressure, minimum 25 PSI and maximum 120 PSI.

### WARRANTY

- 1 YEAR - ALL PARTS
- 5 YEARS - MINERAL TANK
- 5 YEARS - BRINE TANK

DEALER



"SINCE 1936"



MANUFACTURED BY:  
**CAPITAL WATER SOFTENER, INC.**  
 2096 HELENA ST.  
 MADISON, WI 53704  
 608-241-1511